


VENTILATION DUCTS
AND FITTINGS

**ALUMINIUM SEMI
RIGID FLEXIBLE
DUCT 100A (10ft)**



Advantages

- Complete air-tight duct systems!
- Simple on-site assembly!
- No parts fabrication required on the job!
- Standard range of accessories available to permit speedy installation.
- Clean efficient fast installation!
- Greater airflow Life time durability.
- Choice of materials; Aluminium and Stainless Steel for Flexible duct.
- QUALITY job at low cost!

Performance Standards

**Static Pressure 3" to 10" diameters
12" to 18" diameters**

12" (300mm.) W.C. Positive & Negative
8" (200mm.) W.C. Positive & Negative

Maximum Velocity

5000 f.p.m. \ (25m/sec.)

Temperature Range


-100 F to 435 F \ (-73 C to 224 C)

Permeance

Near Zero

CONSTRUCTION

- Type 100 A & 140 A special aluminium alloy prevents corrosion and metal fatigue.
- Close tolerance machine fabrication produces a continuous lock-seam that permits duct to be compressed, pulled open, bent and rebent without developing leakage.



Dimensions

	Bending Radius (Inches)			
Diameter	4	5	6	8
Inside	2	2.5	3	4
Centre-Line	4	5	6	8
Outer 4	6	8	10	12

